



Uso recomendado/recommended end-use:
CAMISETA INTERIOR /
T-SHIRT & KNITTED UNDERWEAR

Composición/composition:
35% Acrílica modificada tipo-F/
Modified acrylic fibre type-F
30% Algodón/Cotton
20% Viscosa/Viscose
14% P-Aramida/P-Aramide
1% Antiestático/Antistatic



LIGAMENTO / LIGAMENT	Interlock	
PESO / WEIGHT (gr/m ²)	190 ± 5%	UNE 40339-2002
ANCHO / WIDTH (cm)	155 ± 1	
PILLING MARTINDALE (5.000 cycles)	4-5	EN 12945-2
ENCOGIMIENTO AL LAVADO / WASHING SHRINKAGE	5%	UNE-EN ISO 15797
INFLAMABILIDAD / INFLAMMABILITY	A1-A2	EN 15025 (EN 11612)
CALOR CONVECTIVO / CONVECTIVE HEAT	BI	ISO 9151
CALOR RADIANTE/ RADIANT HEAT	CI	ISO 6942
CALOR POR CONTACTO / CONTACT HEAT	FI	EN ISO 12127-2
ARCO ELÉCTRICO / ELECTRIC ARC	ATPV: 8.8 cal/cm ²	EN 61482-1-1 (NFPA 70 E)
ALTA VISIBILIDAD / HIGH VISIBILITY	Pass	EN 20471
ANTIESTÁTICO / ANTISTATIC	Pass	EN 1149/3/5

Condiciones de lavado / Washing instructions:



*Evitar utilizar suavizantes / Avoid using softeners