



822 R1 Xispal RS

Uso recomendado/recommended end-use:
POLO / POLO SHIRT

Composición/composition:
30% Acrílica modificada Tipo-F /
Modified acrylic fibre type-f
30% Viscosa / Viscose
20% Algodón / Cotton
19% Poliamida / Polyamide
1% Antistático



LIGAMENTO / LIGAMENT	Jacquard	
PESO / WEIGHT (gr/m ²)	220 ± 5%	UNE 40339-2002
ANCHO / WIDTH (cm)	160 ± 3	
ENCOGIMIENTO AL LAVADO / WASHING SHRINKAGE	5%	EN 6330
INFLAMABILIDAD / INFLAMMABILITY	A1-A2	EN 15025 (EN 11612)
CALOR CONVECTIVO / CONVECTIVE HEAT	B1	ISO 9151
CALOR RADIANTE/ RADIANT HEAT	C1	ISO 6942
CALOR POR CONTACTO / CONTACT HEAT	F1	EN ISO 12127-2
ARCO ELÉCTRICO / ELECTRIC ARC	ATPV: 8.0 cal/cm ² 4kA Class 1	EN 61482-1-1 (NFPA 70 E) EN 61482-1-2
ANTIESTÁTICO / ANTISTATIC	Pass	EN 1149/3/5
ALTA VISIBILIDAD / HIGH VISIBILITY	Pass	EN 20471

Condiciones de lavado EN 6330 (40°C) / Washing instructions EN 6330 (40°C):



*Evitar utilizar suavizantes / Avoid using softeners