



E1Knitted Xispal RS

Uso recomendado/recommended end-use:
PRENDA INTERIOR PARA FUNDICION /
KNITTED WORKWEAR FOR FOUNDRIES

Composición/composition:
50% Algodón / Cotton
39% Acrílica modificada Tipo-F/
Modified acrylic fibre type-F
10% Viscosa / Viscose
1% Antistatic



LIGAMENTO / LIGAMENT	Interlock	
PESO / WEIGHT (gr/m ²)	260 ± 5%	UNE 40339-2002
ANCHO / WIDTH (cm)	160 ± 3	
ENCOGIMIENTO AL LAVADO / WASHING SHRINKAGE	5%	UNE-EN ISO 6330
INFLAMABILIDAD / INFLAMMABILITY	A1-A2	EN 15025 (EN 11612)
CALOR CONVECTIVO / CONVECTIVE HEAT	B1	ISO 9151
CALOR RADIANTE/ RADIANT HEAT	C1	ISO 6942
CALOR POR CONTACTO / CONTACT HEAT	F1	EN ISO 12127-2
RESISTENCIA A LA GRAN SALPICADURA DE HIERRO / IRON BIG SPLASHES (1400OC)	E1	ISO 9185

Condiciones de lavado EN 6330 (40°C) /
Washing instructions EN 6330 (40°C):



*Evitar utilizar suavizantes / Avoid using softeners